



# 110-210-510 Continuous Hinge Shower Door-Framed

[www.bascoshowerdoor.com](http://www.bascoshowerdoor.com)

## Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Door has continuous extruded ball and socket hinge that is integral to the hinge rail jamb
- Hinge assembly has a molded bushing attached at the top and bottom of door panel
- Adjustable jamb provide + 3/8 & -1/4 adjustment on each side of the unit
- Optional towel bar kit



## Calculations

- Maximum allowable width of unit = 36 (@ 72 tall)
- Maximum allowable height of unit = 84 (@ 30 wide)

## Glass Size

- Width = Opening - 4-11/16"
- Height = Unit Height - 3-7/16"

## Metal Cuts

- SC-508 wall jamb = Unit Ht - 7/16"
- SC-549 strike rail = Unit Ht - 1-9/16"
- SC-552 strike jamb = Unit Ht - 7/16"
- SC-589 drip rail = SC-899 bottom rail - 9/16"
- SC-649 hinge jamb = Unit Ht - 7/16"
- SC-648 hinge rail = Unit Ht - 1-9/16"
- SC-899 top and bottom rails = Unit Ht - 2-15/16"
- SC-915 = Unit width

## 110-210-510 Parts List

- A. 1 Curb
- B. 2 Wall Jambs
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1-1/2" Truss Head Screws
- E. 1 Glazed Door Panel
- F. 1 Strike Jamb Magnet
- G. 6 #8 x 1/4" Truss Head Screws
- H. 2 #6 x 1-1/4" Pan Head Screws
- J. 1 Interior Door Handle
- K. 1 Exterior Door Handle
- M. 1 Drip Rail
- N. Tapered Drip Rail
- P. 2 Drip Plugs
- R. 1 Roll of Double Stick Tape
- S. 1 #6 x 3/8" Truss Head Screws

