

Product Features

Tempered safety glass

Options

Glass patterns
Finish



Metal Cuts

- SC702 Curb = Opening - 1/8"
- SC508 Wall Jamb = Unit hgt. + 3/8"
- SC552 Strike Jamb = Unit hgt. + 7/16"
- SC703 #4 Hinge Rail = Unit hgt. - 1 5/8"
- SC706 Hinge Jamb = Unit hgt. + 7/16"
- SC708 #3 Handle Rail = Unit hgt. + 7/16"
- SC711 #2 Center Mag Rail = Unit hgt. + 7/16"
- SC549 #1 Strike Rail = Unit hgt. + 7/16"
- SC899 Hinge Panel Tops =
(Unit Width/2) - 1 5/8"
- SC899 Lead Panel Tops = (Unit Width/2) - 7/8"

Calculations

Maximum allowable width of unit = 36
Maximum allowable height of unit = 67

Glass Size

Door glass ht. = Unit ht. - 3 1/2"
Hinge Panel glass width =
Hinge Panel top - 1 7/8"
Lead Panel glass width =
Lead Panel Top - 1 7/8"

1100 Parts List

- A. 1 Roller Track
- B. 1 Roller Bracket
- C. 2 Nylon Roller Bearings
- D. 2 #8 x 3/8" Hex Head Screws
- E. 2 Wall Jamb
- F. 6 Plastic Wall Anchors
- G. 6 #8 x 1 1/2" Truss Head Screws
- H. 2 #5 x 1/2" Truss Head Screws
- J. 1 Glazed Bi-Fold Panel Assembly
- K. 1 Strike Jamb
- M. 1 Headless Pivot Pin Screw
- N. 6 #8 x 3/8" Truss Head Screws
- P. 1 Clear Vinyl Deflector (36")
- R. 1 Interior Handle
- S. 1 Exterior Handle
- T. 2 #6-32 x 1 1/4" Round Head Screws
- U. 1 BASCO Decal

