

Product Features

Available in standard and custom configuration
Tempered safety glass
Pivot jambs to have a continuous vinyl seal
Top pivot pin to have safety washer to prevent accidental dislodging of the door

Metal Cuts

SC-505 header = Centerline dim. + 3/8
SC-505A curb = Centerline dim. + 3/8
SC-505 return header = Centerline dim. + 3/16
SC-505A return curb = Centerline dim. + 3/16
SC-506 head and curb fill = Top and bottom rail + 3/8
SC-508 wall jamb = Unit ht. - 3/4
SC-512 135° post = Unit ht. - 3/4
SC-522P pivot jamb = Unit ht. - 2
SC-552S strike jamb = Unit ht. - 2
SC-589 drip rail = door glass - 15/16
SC-558 bottom rail = door glass - 4 5/8

161-761 Parts List

A. 3 Curb Sections (with weep slots)
B. 4 135° Anchor Plates
C. 48 #8 x 1/4" Truss Head Screws
D. 3 Header Sections
E. 2 Wall Jamb
F. 6 Plastic Wall Anchors
G. 6 #8 x 1 1/2" Truss Head Screws
H. 4 Plastic Setting Blocks
J. 2 Fixed Glass Panels
K. 2 135° Posts
L. 1 Clear Vinyl Pivot Jamb Seal
M. 1 Pivot Jamb
N. 1 Strike Jamb Assy (Magnetic)
P. 2 Snap-in Fillers
R. 1 Glazed Door Panel
S. 1 Bottom Rail (See Note)
T. 1 Drip Rail
U. 1 Roll Double Stick Tape
V. 1 Tapered Drip Vinyl
W. 2 #10 x 7/16" Set Screws
X. 2 Pivot Blocks
Y. 1 Nylon Spacer
AA. 2 Nylon Pivot Bushings
BB. 1 Security Washer
CC. 1 Door Handle Assy
DD. 1 Door Handle Vinyl (8")
EE. 2 Drip Plugs
FF. 1 #6 x 3/8" Truss Head Screws
GG. 4 Rail End Caps
HH. 1 BASCO Decal
JJ. 8 Pcs. Vert. Glazing Vinyl (72")
KK. 4 Pcs. Horiz. Glazing Vinyl (72")

Options

Glass patterns
Finish

Calculations

Maximum allowable width of unit = 72
Maximum allowable height of unit = 84

Glass Size

Door glass width = centerline dim. - 2 5/8
Door glass ht. = Unit ht. - 5
Panel glass width = Centerline dim. - 13/16
Panel glass ht. = Unit ht. - 1

Picture of 160-760 FRAMED unit

