

Product Features

Available in standard and custom configuration
 3/8 Tempered safety glass
 Adjustable sealed heavy duty ball bearing rollers
 Up and down adjustment of panels is $\pm .156$
 Safety tee-lock wall jamb to header connection
 Pocketed wall jambs for superior leak prevention
 Transparent molded panel guide for inconspicuous control of sliding panels

Options

Anti-jamb header insert
 Wall fill
 Curb fill
 Glass patterns
 Finish



Calculations

Maximum allowable width of unit = 72 (@ 71 1/4 tall)
 Maximum allowable height of unit = 84 (@ 60 wide)

Glass Size

Width = (Unit Width \div 2) + 1/4
 Height = Unit Ht. - 2 3/8

Metal Cuts

SC-623 header = Unit width - 1/16
 SC-624 tub track = Unit width - 1/16
 SC-625 wall jamb = Unit ht. - 1 3/8

2850-3850 Parts List

- A. 2 Wall Jambs
- B. 1 Tub Track with Vinyl
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 4 Clear Jamb Bumpers
- F. 2 Nylon T-Locks
- G. 1 Header
- H. 4 Hanger Brackets
- J. 2 Glass Door Panels
- K. 8 Nylon Bushings (.360 long)
- L. 4 1/4 x 5/8 Flat Head Screws
- M. 4 HD Roller Bearings
- N. 4 #8 x 3/8 Hex Head Screw
- P. 2 Towel Bar Caps (w/Post)
- R. 8 Flat Rubber Washers
- S. 4 Handle Bases (Threaded)
- T. 4 #8 x 5/8 Flat Head Screws
- U. 2 Acrylic Towel Bar Assemblies
- V. 3 Clear Panel Guides
- W. 3 #6 x 3/8 Pan Head Screws
- X. 2 Nylon Jamb Covers

