

Product Features

Available in standard and custom configuration
Tempered safety glass
Adjustable sealed heavy duty ball bearing rollers
Up and down adjustment of panels is $\pm .156$
Safety tee-lock wall jamb to header connection
Molded jamb bumpers

Metal Cuts

SC-881 header = Unit width - 1/16
SC-556 tub track = Unit width - 1/16
SC-896 wall jamb = Unit ht. 1 1/2
SC-882 top rail = (Unit width / 2) - 1/8
SC-883 bottom rail = (Unit width / 2) - 1/8
SC-884 side rail = Unit ht. - 2 5/8

Options

Anti-jamb header insert
Wall fill
Curb fill
Glass patterns
Finish

Calculations

Maximum allowable width of unit = 72
Maximum allowable height of unit = 72

Glass Size

Width = (Unit Width / 2) - 2
Height = Unit Ht. - 4 1/2



6150-7150 Parts List

- A. 1 TubTrack with Vinyl
- B. 2 Wall Jamb
- C. 6 Plastic Wall Plugs
- D. 6 #8 x 1 1/2" Truss Head Screws
- E. 2 Nylon spacers
- F. 1 Header
- G. 2 Glazed Panels
- H. 4 Nylon Roller Bearings
- J. 4 #8-32 x 3/8" Hex Head Screws
- K. 4 Towel Bar Trim Rings
- L. 2 Towel Bars
- N. 2 #10-24 x 7/8" Truss Head Screws
- P. 2 #10-24 x 1 1/8" Flat Head Screws
- R. 2 Acrylic Finger Pulls
- S. 2 BASCO Decals
- T. 1 Nylon Bottom Guide
- U. 1 #6 x 3/8" Pan Head Screw
- V. 2 Stainless Bumper Inserts
- W. 2 Soft Jamb Bumpers

